

Technical Data Sheet

Bode 100 Revision 1

Vector Network Analyzer



V2.20

© 2021 by OMICRON Lab

Visit www.omicron-lab.com for more information.

Contact support@omicron-lab.com for technical support.

Technical data subject to change without notice.



1. Signal Source (OUTPUT)

Waveform	Sinusoidal signal
Frequency range	1 Hz to 40 MHz
Signal level	-30 dBm to 13 dBm 0.007 V _{RMS} to 1 V _{RMS} (@ 50 Ω load)
Source level accuracy	± 0.3 dB (1 Hz to 1 MHz) ± 0.6 dB (1 MHz to 40 MHz)
Source level frequency response (flatness)	± 0.3 dB (typical, referring to 10 MHz)
Frequency stability	± 15 ppm* (< 1 year after adjustment) ± 25 ppm* (< 3 years after adjustment) *± quantisation error (= 0.5 · step size)
Frequency step size / resolution	0.03492 Hz
Source impedance	50 Ω
Return loss (1 Hz to 40 MHz)	> 28 dB (VSWR < 1.09)
Spurious signals	< -55 dBc (typical)
Harmonics	< -55 dBc (typical)
Connector type	BNC

2. Inputs (CH1, CH2)

Input impedance (software switchable)	High: 1 MΩ ± 2% 40...55 pF Low: 50 Ω
Return loss @ 50 Ω input impedance	> 25 dB (1 Hz to 40 MHz)
Receiver bandwidth - RBW (software selectable)	1 Hz, 3 Hz, 10 Hz, 30 Hz, 100 Hz, 300 Hz, 1 kHz, 3 kHz
Noise floor (S21 measurement) RBW = 10 Hz, P _{SOURCE} = 13 dBm, Attenuator CH1: 20 dB, CH2: 0 dB	1 Hz to 5 kHz: -100 dB (typical) 5 kHz to 50 kHz: -110 dB (typical) 50 kHz to 20 MHz: -115 dB (typical) 20 MHz to 40 MHz: -110 dB (typical)
Input attenuators (software selectable)	0 dB, 10 dB, 20 dB, 30 dB, 40 dB
Input sensitivity / range	100 mV _{RMS} full scale @ 0 dB input attenuator 10 V _{RMS} full scale @ 40 dB input attenuator
Input channels dynamic range	> 100 dB (@ 10 Hz RBW)
Gain error	< 0.1 dB (User-Range calibrated)
Phase error	< 0.5° (User-Range calibrated)
Connector type	BNC

Technical data subject to change without notice.

3. USB Interface

Connector	Type B
-----------	--------

4. PC Requirements

Processor	Intel Core-I Dual-Core (or similar)
Memory (RAM)	2 GB, 4 GB recommended
Graphics resolution	Super VGA (1024 x 768) higher resolution recommended
Graphics card	DirectX 11 with Direct2D support
USB interface	USB 1.1 or higher
Operating system	Windows 10 required for BAS 3.24 or newer

5. Power Requirements

AC/DC power adapter

Input voltage / frequency	100...240 V / 47...63 Hz
---------------------------	--------------------------

DC power requirements

Supply voltage range / power	+10... 24 V / <10 W
Supply current	at 12 V: 450 mA (typical) at 18 V: 300 mA (typical) at 24 V: 230 mA (typical)
Low supply voltage shut-down	8.25 V (typical)
Power connector / socket	Coaxial power socket Inner diameter 2.5 mm Outer diameter 5.5 mm
Connector polarity	Inner connector ... positive Outer connector ... ground

Technical data subject to change without notice.

6. Environmental Requirements

Temperature range	Storage	-35...+60 °C / -31...+140 °F
	Operating	+5...+40 °C / +41...+104 °F
	For specifications	23 °C ± 5 °C / 73 °F ± 18 °F
Relative humidity	Storage	20...90 %, non-condensing
	Operating	20...80 %, non-condensing

7. General

Dimensions (width × height × depth)	26 cm x 5 cm x 26.5 cm 10.25 inch x 2 inch x 10.5 inch
Weight - Bode 100	< 2 kg/4.4 lb
Weight - Accessories	< 0.5 kg/1.1 lb

8. Absolute Maximum Ratings (device will be destroyed)

DC supply voltage	+28 V
DC supply reverse voltage	-28 V
Maximum input signal at CH1 or CH2 (low impedance, 50 Ω)	1 W (= 7 V _{RMS})
Maximum AC input signals at CH1 or CH2 (high impedance 1 MΩ)	50 V _{RMS} 1 Hz to 1 MHz
	30 V _{RMS} 1 MHz to 2 MHz
	15 V _{RMS} 2 MHz to 5 MHz
	10 V _{RMS} 5 MHz to 10 MHz
	7 V _{RMS} 10 MHz to 40 MHz
Maximum DC input signal at CH1 or CH2 (high impedance, 1 MΩ)	50 V
Maximum return power at the OUTPUT connector	0.5 W (= 5 V _{RMS})

V2.20

© 2021 by OMICRON Lab

Visit www.omicron-lab.com for more information.

Contact support@omicron-lab.com for technical support.